

Machine Description



56000










Original Design Flatbed One, Two, and Three Needle Chainstitch

- Seaming operations on light to medium weight fabrics - 56300 styles. Single needle general seaming for a variety of sewn products.
- Lapseaming operations on medium to heavy weight fabrics - 56500 styles. Two needle full felled seaming for denim products.
- Lapseaming operations on medium to heavy weight fabrics - 56900 styles. Three needle full felled seaming for denim products.

Machine Specifications



Model	56300F/R	56300G	56300AV	56300V	56500R	56900P/R
Needle	128GBS080/032~150/060		130GHS080/032~140/054		147GKS090/036~140/054 standard 125/049	
	standard 090/036	standard 080/032	standard 100/040	standard 090/036		
Material Weight	light to medium	medium	medium	light to medium	medium to heavy	
Stitch Length Adj.	by adjusting screw					
Needle Bar Stroke	30.5mm				33.4mm	
Lubrication	automatic					
Lubricating Oil	Union Special Spec 175 (ISO grade 22)					
Stitch Type	401					
Seam Type	SSa-1				LSo-2	LSo-3

							
56300F	1	2	-	2.1~3.6 (3.2 standard)	6.4mm	6500 RPM	
56300G	1	2	-	1.8~2.5 (2.1 standard)	6.4mm	6500 RPM	
56300R	1	2	-	2.1~3.6 (3.2 standard)	6.4mm	6000 RPM	

56300AV	1	2	-	2.5~4.2 (3.2 standard)	4.8mm	6500 RPM
56300V	1	2	-	1.6~2.8 (2.1 standard)	4.8mm	6500 RPM
56500R16	2	4	6.4mm	1.8~3.6 (3.2 standard)	6.4mm	6000 RPM
56500R18	2	4	7.2mm	1.8~3.6 (3.2 standard)	6.4mm	6000 RPM
56900P8	3	6	3.2mm	1.8~3.6 (3.2 standard)	8mm	6000 RPM
56900P9	3	6	3.6mm	1.8~3.6 (3.2 standard)	8mm	6000 RPM
56900R8	3	6	3.2mm	1.8~3.6 (3.2 standard)	8mm	6000 RPM
56900R9	3	6	3.6mm	1.8~3.6 (3.2 standard)	8mm	6000 RPM