



-
- 81200 A**
- Overedging machine for overseaming on medium to heavy weight jute and burlap bags. Seam width 10 mm.
 - Sewing capacity up to 16 mm.
 - Plain feed, max. speed 2000 RPM, stitch type 502.
 - Needle: 1
 - Threads: 2
 - Stitch range: 2 - 4.25 spi
-
- 81200 AZ 3281**
- Same as 81200 A, but seam width 18mm.
-
- 81200 B**
- Same as 81200 A, but seam width 6 mm.
 - For overseaming on light to heavy weight bag and linen material.
 - Needle: 1
 - Threads: 2
 - Stitch range: 2 - 4.25 spi
-
- 81200AB**
- Overedging machine for overseaming heavy weight jute, burlap or woven polypropylene bags.
 - 12mm overedge width. Sewing capacity up to 16mm.
 - Plain feed, max speed of 2000 RPM. Stitch type 506 Ssa-1.
 - Needle: 2
 - Thread: 4
 - Stitch range: 2 - 4.25 spi
-
- 81200 D**
- Overedging machine for binding woollen blankets, horse blankets, felt, etc...
 - 12mm overedge seam width.
 - Sewing capacity up to 12mm.
 - Plain feed, max speed 2000RPM, stitch type 503 EFd-1.
 - Needle: 1
 - Thread: 1
 - Stitch range: 1.5 - 3.2mm
-
- 81200 E**
- For butted seams for dyeing and finishing as well as geotextile, felt and filter applications.
 - Seam width 10 mm, fabric thickness up to 16 mm.
 - Plain feed, max. speed 1600 RPM, stitch type 501.
 - Needle: 1
 - Thread: 1
 - Stitch range: 10-19 mm
 - Standard: 14 mm
-
- 81200 EZ 3254**
- Same as 81200 E, but with upper feed.
 - Fabric thickness up to 20 mm. Max. speed 1200 RPM.
 - Needle: 1
 - Thread: 1
 - Stitch range: 6-13 mm
 - Standard: 10 mm

• Standard: 12 mm

81200 J

- Overedging machine for binding wool blankets, horse blankets, felt, etc...
- 12mm overedge seam width.
- Sewing capacity up to 12mm.
- Plain feed, max speed 2000RPM, stitch type 504 EFd-1.