


■ Numbering of Model

AZ7020SD-Y5DF-8/K2



- ① Symbol of series
- ② Class No.: 70,71 = Overlock, 75 = Safety stitch
- ③ Submodel
- ④ Needle distance: O = Single needle, X = 2mm, Y = 2.4mm, A = 3.2mm, C = 5mm
- ⑤ Overedge seam width: 2 = 2mm, 4 = 4mm, 5 = 5mm, 6 = 6mm, 7=7mm, 8=8mm
- ⑥ Feeding mode: D = Differential Feed
- ⑦ Type of Upper Knife: F = Flat Knife
- ⑧ Special Specification
- ⑨ Devices

■ Specification

Model	Seam	1	2	3	4	5	6	7	8	9
AZ7003SD-8		1	3	-	4					6
AZ7020SD-8		2	4	2	4					6
AZ7025SD-8		2	4	2	4					6
AZ7120SD-8		2	4	2.4	5, 6	1-4				6
AZ7125SD-8		2	4	2.4	5, 6					6
AZ7500SD-8		2	5	3.2	4					6
AZ7520SD-8		3	6	3.2+2.4	6					6

■ Device

- K1: Automatic Thread Chain Cutter (Horizontal Type)
- K2: Automatic Thread Chain Cutter (Vertical Type)
- B3: Back-tacker
- BT43: Semi-Automatic Back-tacker
- MT22: Tape Cutter

Prevent oil stain by greasy dust

SC□□: Self Cleaning System (Options)

It eliminates accumulating of dust around the lower knife and the area under stitch plate and ensures clean operation environment.

- ➔ Blowing off lint (uses an oil cooling fan which cools off oil.)
- ➔ Collecting lint (for lint collection, an optional vacuum cleaner is recommended.)

Lint Accumulating Area

Suction

Air Blow

Without SC

With SC