

BEW single needle series

Specifications (BEW-□)

| Variety | BEW-8BLE | BEW-8BLCE | BEW-8BLCE-BTFL-CD-DS |
|-------------------------------------|--|--|----------------------|
| Number of needle | Single needle | | |
| Max. sewing speed | 2,500s.p.m. (Refer to list below) | | |
| Max. stitch length | 9mm (Forward / Reverse) | | |
| Clearance under presser foot | 9mm (by hand) 16mm (by knee) | 9mm (by hand) 16mm (by automatic foot lifter) | |
| Needle bar stroke | 37mm | | |
| Needle | 135×17 Nm110~Nm200 (Nm160) or DP×17 #18~#25 (#23) | | |
| Thread | #30~#1 (Standard #5) | | |
| Hook | Large vertical axis hook (2.0 times) | | |
| Thread length after trimming | - | Approx. 1/2" | |
| Thread take up lever | Slide type | | |
| Amount of walking foot movement | 1~6.5mm | 1~7mm | |
| Walking foot movement change switch | Dial type | | |
| Bobbin winder | Built-in type located at the top of the sewing machine | | |
| Auto presser foot lifting device | - | Pneumatic | |
| Walking foot movement change device | - | Pneumatic | |
| Safety device | Standard | | |
| Lubrication | Automatic lubrication type | | |
| Bed size/Working space | 567mm×177mm / 300mm×120mm | | |
| Net weight (Head only) | 49Kg | 50Kg | 51Kg |
| Motor | Clutch motor | AC Servo motor (0.75kw) | |