

							Needle No.	S.P.M. (Max)	
C007J-W512-240/FE	2	4	4.0	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS# 10	4500	
C007J-W512-248/FE	2	4	4.8	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS# 10	4500	
C007J-W512-356/FE	3	5	5.6	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS# 10	4500	
C007J-W512-364/FE	3	5	6.4	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS# 10	4500	
C007JD-W512-240/FE	2	4	4.0	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS# 10	4500	
C007JD-W512-248/FE	2	4	4.8	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS# 10	4500	
C007JD-W512-356/FE	3	5	5.6	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS# 10	4500	
C007JD-W512-364/FE	3	5	6.4	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS# 10	4500	



DESCRIPTION

ELECTRIC ELASTIC OR LACE ATTACHING

Elastic feeding evenly length and elasticity controlled by electronic digital control box, for elastic or lace attaching smoothly and properly on women's underwears.

Remark:

The maximum width of elastic tape is 2-1/2"



OPTION

DEVICE	MOTOR			TABLE
.CL .LF-A .CL/LF-A	Model	Clutch	Servo	C007-T23 C007-T25
	C007J	T32xxHx	T72xx	
	C007JD	-	TA401xx T6400xx	

STANDARD



FE (J)

ELECTRIC TYPE ELASTIC FEEDING

1. Elastic feeding evenly length and elasticity controlled by electronic digital control box.
2. Maximum feeding width of elastic is 2-1/2".

Available Model:

- C007J-W512, C007JD-W512
 C007J-W522, C007JD-W522
 F007J-W512, F007JD-W512
 F007J-W522, F007JD-W522