

								
C007J-W512-240/FFC	2	4	4.0	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS#10	4500
C007J-W512-248/FFC	2	4	4.8	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS#10	4500
C007J-W512-356/FFC	3	5	5.6	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS#10	4500
C007J-W512-364/FFC	3	5	6.4	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS#10	4500
C007JD-W512-240/FFC	2	4	4.0	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS#10	4500
C007JD-W512-248/FFC	2	4	4.8	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS#10	4500
C007JD-W512-356/FFC	3	5	5.6	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS#10	4500
C007JD-W512-364/FFC	3	5	6.4	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS#10	4500

**DESCRIPTION**

**MECHANIC ELASTIC OR LACE ATTACHING**

Elastic feeding evenly length and elasticity controlled by gear set. For elastic or lace attaching smoothly and properly on women's underwears.

Remark : The maximum width of elastic tape is 2-1/2"



**OPTION**

DEVICE	MOTOR			TABLE
	Model	Clutch	Servo	
.CL .LF-A .CL/LF-A	C007J	T32xxHx	T72xxKHE	C007-T23 C007-T25
	C007JD	-	TA401xx T6400xx	

**STANDARD**



**FFC (J)**

**MECHANIC TYPE ELASTIC FEEDING DEVICE**

1. Elastic feeding evenly length and elasticity controlled by gear set.
2. Maximum feeding width of elastic is 2-1/2"

**Available Model:**

- C007J-W512, C007JD-W512
- C007J-W522, C007JD-W522
- F007J-W512, F007JD-W512
- F007J-W522, F007JD-W522