			-₩-	00	####	mm I	Needle No.	S.P.M. (Max)
C007J-W522-356/CR/FFC	3	5	5.6	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS#11	4500
C007J-W522-364/CR/FFC	3	5	6.4	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS#11	4500
C007JD-W522-356/CR/FFC	3	5	5.6	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS#11	4500
C007JD-W522-364/CR/FFC	3	5	6.4	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS#11	4500



DESCRIPTION

ELASTIC / LACE ATTACHING WITH RIGHT SIDE FABRIC TRIMMER

Elastic feeding evenly length and elasticity controlled by gear set. With right hand side fabric trimmer for elastic or lace attaching smoothly and properly on women's underwears.



OPTION

DEVICE		TABLE			
.CL .LF-A .CL/LF-A	Model	Clutch	Servo		
	C007J	T32xxHx	T72xx	C007-T25	
	C007JD	-	TA401xx T6400xx		

STANDARD



CRRIGHT HAND SIDE TRIMMER

Right hand side waste fabric trimming with waste suction device makes fabric edge aligned to seam and keeps the working area clean.

Available Model:

C007J-W522,C007JD-W522

Self-installation: N



FFC (J) MECHANIC TYPE ELASTIC FEEDING DEVICE

- 1. Elastic feeding evenly length and elasticity controlled by gear set.
- 2. Maximum feeding width of elastic is 2-1/2"

Available Model

C007J-W512, C007JD-W512 C007J-W522, C007JD-W522 F007J-W512, F007JD-W512 F007J-W522, F007JD-W522