C18

	Į		.₩.	00		mm T	Needle No.	S,P,M. (Max)
C007J-W822-240/CRL/CY	2	4	4.0	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS#10	4500
C007J-W822-356/CRL/CY	3	5	5.6	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS#10	4500
C007J-W822-364/CRL/CY	3	5	6.4	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS#10	4500
C007JD-W822-240/CRL/CY	2	4	4.0	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS#10	4500
C007JD-W822-356/CRL/CY	3	5	5.6	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS#10	4500
C007JD-W822-364/CRL/CY	3	5	6.4	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS#10	4500



DESCRIPTION

PNEUMATIC TUBULAR ELASTIC INSERTING

With pneumatic driving folder to fold fabric and insert elastic smoothly, left hand side fabric trimming before hemming increases sewing quality & efficiency. For hemming sleeve opening and bottom of underwears, T-shirt or sportswear etc.



OPTION

DEVICE		TABLE			
.UTP					
.UTQ .CL	Model	Clutch	Servo		
.RL .UTP/CL .UTQ/CL	C007J	T32xxHx	T72xx T74xx	C007-T25	
.UTP/RL .UTQ/RL .UTP/CL/RL	C007JD	-	TA401xx T6400xx		
.UTQ/CL/RL					

STANDARD



CRL LEFT HAND SIDE TRIMMER

Left hand side fabric trimming makes fabric edge aligned to seam.

Available Model:

C007J-W812, C007JD-W812 C007J-W822, C007JD-W822

Self-installation : N



CY PNEUMATIC ELASTIC INSERTING DEVICE

Pneumatic tubular elastic inserting device is convenient to operate and sew efficiently.

Available Mode

C007J-W532, C007JD-W532