	Į		.₩.	00	####	mm	Needle No.	S.P.M. (Max)
C007J-W121-356/CH	3	5	5.6	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS#10	6000
C007J-W121-364/CH	3	5	6.4	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS#10	6000
C007JD-W121-356/CH	3	5	5.6	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS#10	6000
C007JD-W121-364/CH	3	5	6.4	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS#10	6000



DESCRIPTION

GENERAL SEAMING / BOTTOM HEMMING

Regular cover stitching by 3 needle 5 thread chainstitch cylinder bed machine, can be attached with hemming set for various sewing. Such as plain seaming and bottom hemming for underwear, sportswear etc. (For light material)



OPTION

DEVICE		TABLE		
.UTP	Model	Clutch	Servo	
.UTQ .UTR .UTS .CLA .CLAUTP .CLAUTQ .CLAUTR .CLAUTS	C007J	ТЗ2ххНх	T72xx T74xx	C007-T23 C007-T25
	C007JD	-	TA401xx T6400xx	

STANDARD



CH HEMMING

Suitable for the bottom hemming of T-shirt, underwear, cuff of children's garment,etc... Able to adjust the width of hemming set to fit demands, esay operation.

Available Model:

C007J-W121, C007JD-W121 C007J-W122, C007JD-W122 C007J-W123, C007JD-W123 C007J-W162, C007JD-W162 C007K-W121, C007KD-W121 C007K-W122, C007KD-W122 C007K-W123, C007KD-W123 C007K-W162, C007KD-W162