	Ī		.₩.	00		mm	Needle No.	S.P.M. (Max)
C007J-W123-240/CH	2	4	4.0	1:0.3~1:2.9	1.4~3.6	5~7	UYX128GAS#10	6000
C007J-W123-248/CH	2	4	4.8	1:0.3~1:2.9	1.4~3.6	5~7	UYX128GAS#10	6000
C007J-W123-356/CH	3	5	5.6	1:0.3~1:2.9	1.4~3.6	5~7	UYX128GAS#10	6000
C007J-W123-364/CH	3	5	6.4	1:0.3~1:2.9	1.4~3.6	5~7	UYX128GAS#10	6000
C007JD-W123-240/CH	2	4	4.0	1:0.3~1:2.9	1.4~3.6	5~7	UYX128GAS#10	6000
C007JD-W123-248/CH	2	4	4.8	1:0.3~1:2.9	1.4~3.6	5~7	UYX128GAS#10	6000
C007JD-W123-356/CH	3	5	5.6	1:0.3~1:2.9	1.4~3.6	5~7	UYX128GAS#10	6000
C007JD-W123-364/CH	3	5	6.4	1:0.3~1:2.9	1.4~3.6	5~7	UYX128GAS#10	6000



## **DESCRIPTION**

# **GENERAL SEAMING / BOTTOM HEMMING**

Regular cover stitching, can be attached with hemming set for various sewing. Such as plain seaming and bottom hemming for underwear, sportswear etc. (For heavy material)



## **OPTION**

DEVICE		TABLE		
.UTP	Model	Clutch	Servo	
.UTQ .UTR .UTS .CLA	C007J	T32xxHx	T72xx T74xx	C007-T23 C007-T25
.CLAUTP .CLAUTQ .CLAUTR .CLAUTS	C007JD	-	TA401xx T6400xx	





#### CH HEMMING

Suitable for the bottom hemming of T-shirt, underwear, cuff of children's garment,etc... Able to adjust the width of hemming set to fit demands, esay operation.

#### Available Model:

C007J-W121, C007JD-W121 C007J-W122, C007JD-W122 C007J-W123, C007JD-W123 C007J-W162, C007JD-W162 C007K-W121, C007KD-W121 C007K-W122, C007KD-W122 C007K-W123, C007KD-W123 C007K-W162, C007KD-W162