


	Needle		Stitch	Stitch Length	Stitch Width	Stitch Density	Needle No.	S.P.M. (Max)
C007J-W162-240/CH	2	4	4.0	1:0.3~1:2.9	1.4~3.6	5~7	TVX5#14~#16	6000
C007J-W162-248/CH	2	4	4.8	1:0.3~1:2.9	1.4~3.6	5~7	TVX5#14~#16	6000
C007J-W162-356/CH	3	5	5.6	1:0.3~1:2.9	1.4~3.6	5~7	TVX5#14~#16	6000
C007J-W162-364/CH	3	5	6.4	1:0.3~1:2.9	1.4~3.6	5~7	TVX5#14~#16	6000
C007JD-W162-240/CH	2	4	4.0	1:0.3~1:2.9	1.4~3.6	5~7	TVX5#14~#16	6000
C007JD-W162-248/CH	2	4	4.8	1:0.3~1:2.9	1.4~3.6	5~7	TVX5#14~#16	6000
C007JD-W162-356/CH	3	5	5.6	1:0.3~1:2.9	1.4~3.6	5~7	TVX5#14~#16	6000
C007JD-W162-364/CH	3	5	6.4	1:0.3~1:2.9	1.4~3.6	5~7	TVX5#14~#16	6000



DESCRIPTION

GENERAL SEAMING/BOTTOM HEMMING

Regular cover stitching, suitable for heavy material. Can be attached with hemming set for various sewing. Such as plain seaming and bottom hemming for underwear, sportswear etc. (For heavy material)



OPTION

DEVICE	MOTOR			TABLE
	Model	Clutch	Servo	
.UTP	C007J	T32xxHx	T72xx	C007-T23 C007-T25
.UTQ				
.UTR			TA401xx	
.UTS				
.CLA	C007JD	-	-	
.CLA/UTP				
.CLA/UTQ				
.CLA/UTR				
.CLA/UTS				

STANDARD



CH HEMMING

Suitable for the bottom hemming of T-shirt, underwear, cuff of children's garment, etc... Able to adjust the width of hemming set to fit demands, easy operation.

Available Model:

- C007J-W121, C007JD-W121
- C007J-W122, C007JD-W122
- C007J-W123, C007JD-W123
- C007J-W162, C007JD-W162
- C007K-W121, C007KD-W121
- C007K-W122, C007KD-W122
- C007K-W123, C007KD-W123
- C007K-W162, C007KD-W162