

							Needle No.	S.P.M. (Max)	
C007K-W512-240/FE	2	4	4.0	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS#10	4500	
C007K-W512-248/FE	2	4	4.8	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS#10	4500	
C007K-W512-356/FE	3	5	5.6	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS#10	4500	
C007K-W512-364/FE	3	5	6.4	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS#10	4500	
C007KD-W512-240/FE	2	4	4.0	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS#10	4500	
C007KD-W512-248/FE	2	4	4.8	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS#10	4500	
C007KD-W512-356/FE	3	5	5.6	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS#10	4500	
C007KD-W512-364/FE	3	5	6.4	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS#10	4500	




DESCRIPTION

ELECTRIC ELASTIC OR LACE ATTACHING

Elastic feeding ensures evenly length and elasticity, controlled by electronic digital control box, for elastic or lace attaching smoothly and properly on women's underwears.

Remark:

The maximum width of elastic tape is 2-1/2"



OPTION

DEVICE	MOTOR			TABLE
	Model	Clutch	Servo	
.CL .LF-A	C007K	T32xxHx	T72xx	C007K-T23 C007K-T25
.CL/LF-A	C007KD	-	TA401xx T6421xx	