

									S.P.M. (Max)
C007K-W512-240/FFC	2	4	4.0	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS#10	4500	
C007K-W512-248/FFC	2	4	4.8	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS#10	4500	
C007K-W512-356/FFC	3	5	5.6	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS#10	4500	
C007K-W512-364/FFC	3	5	6.4	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS#10	4500	
C007KD-W512-240/FFC	2	4	4.0	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS#10	4500	
C007KD-W512-248/FFC	2	4	4.8	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS#10	4500	
C007KD-W512-356/FFC	3	5	5.6	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS#10	4500	
C007KD-W512-364/FFC	3	5	6.4	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS#10	4500	




DESCRIPTION

MECHANIC ELASTIC OR LACE ATTACHING

Elastic feeding ensures evenly length and elasticity, controlled by gear set. For elastic or lace attaching smoothly and properly on women's underwears.

Remark : The maximum width of elastic tape is 2-1/2"



OPTION

DEVICE	MOTOR			TABLE
	Model	Clutch	Servo	
.CL .LF-A .CL/LF-A	C007K	T32xxHx	T72xx	C007K-T23 C007K-T25
	C007KD	-	TA401xx T6421xx	