

C17


							Needle No.	S.P.M. (Max)	
C007K-W812-240/CRL	2	4	4.0	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS#10	4500	
C007K-W812-356/CRL	3	5	5.6	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS#10	4500	
C007K-W812-364/CRL	3	5	6.4	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS#10	4500	
C007KD-W812-240/CRL	2	4	4.0	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS#10	4500	
C007KD-W812-356/CRL	3	5	5.6	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS#10	4500	
C007KD-W812-364/CRL	3	5	6.4	1:0.3~1:2.9	1.4~3.6	5	UYX128GAS#10	4500	



DESCRIPTION

BOTTOM HEMMING WITH LEFT SIDE FABRIC TRIMMER

Left hand side fabric trimming before hemming. For sleeve opening and bottom of underwears, T-shirt or sportswear, etc...



OPTION

DEVICE	MOTOR			TABLE
	Model	Clutch	Servo	
.UTP	C007K	T32xxHx	T72xx	C007K-T25
.UTQ			T74xx	
.CL	C007KD	-	TA401xx	
.UTP/CL			T6421xx	
.UTQ/CL				