

C19

| C007K-W922-456/CW | 4 | 6 | 5.6 | 1:0.3~1:2.9 | 1.4~3.6 | 5 | SMX1014B#10 | 6000 |
|--------------------|---|---|-----|-------------|---------|---|-------------|------|
| C007K-W922-464/CW | 4 | 6 | 6.4 | 1:0.3~1:2.9 | 1.4~3.6 | 5 | SMX1014B#10 | 6000 |
| C007KD-W922-456/CW | 4 | 6 | 5.6 | 1:0.3~1:2.9 | 1.4~3.6 | 5 | SMX1014B#10 | 6000 |
| C007KD-W922-464/CW | 4 | 6 | 6.4 | 1:0.3~1:2.9 | 1.4~3.6 | 5 | SMX1014B#10 | 6000 |




DESCRIPTION

FLAT SEAMING

For flat seaming 2 pieces of fabric. Equipped with fabric guide for easy operation.

OPTION



| DEVICE | MOTOR | | | TABLE |
|---------|--------|---------|----------------|------------------------|
| | Model | Clutch | Servo | |
| .UTP | | | | C007K-T23 C007K-T25 |
| .UTQ | | | | |
| .UTR | | | | |
| .UTS | C007K | T32xxHx | T72xx T74xx | |
| .CL | | | | |
| .UTP/CL | | | | |
| .UTQ/CL | | | TA401xx | |
| .UTR/CL | C007KD | - | T6421xx | |
| .UTS/CL | | | | |