

■ Numbering on Model:

CM-3 51/AT



① Symbol of Series

② Class No. : 3 = Standard

③ Submodel by Application

④ Device(s)

AT : Automatic Thread Trimmer

T : Manual Thread Trimmer

AL : Automatic Presser Foot Lowering Device

TS* : Automatic Thread Trimmer with Automatic
Stitch Fastening Device.

TF : Automatic Thread Fastening Device

TP : Thread Pull-off Device

■ Specifications

LW × 6T 1	1	-	3.2~8.5	1:1 - 1:1.5	-	10	-	3000	-	-

Except models without differential feed.

■ Submodels

Model	Applications / Remarks	Skip Stitch Mechanism
CM-351	For felling sewing on light to medium weight fabrics.	—
CM-352	For felling (blindstitching) on light to medium weight fabrics	○
CM-355	Exclusive for sewing bottom of trousers.	—
CM-356	Exclusive for lapel and collar padding.	—
CM-357	For blindstitching in the waist lines. With Automatic Depressing Plunger For medium weight fabrics	—
CM-359	For bookseaming on coat's backs.	—
CM-360	For pintacking on slacks, skirts, training pants, etc.	○
CM-364	For shirring operation on flare skirts, etc. With differential feed (Differential ratio 1:1~1:1.5)	○
CM-367	For blindstitching waist lining on trousers and other heavy weight material. With automatically depressed plunger. No thread pull over cross seam. The upper cloth layer only is being pierced.	—
CM-370	For making 4 folded belt loops. With trimming knives for cutting both edges of material.	—
CM-374	Pedal switch feeding control type machine, which enables shirring during sewing. With differential feed (Differential ratio 1:1 ` 1:1.5)	○