
	
F007J-W512-240/FFC	2	4	4.0	1:0.5~1:1.3	1.2~4.0	5~7	UYX128GAS#10	4500
F007J-W512-248/FFC	2	4	4.8	1:0.5~1:1.3	1.2~4.0	5~7	UYX128GAS#10	4500
F007J-W512-356/FFC	3	5	5.6	1:0.5~1:1.3	1.2~4.0	5~7	UYX128GAS#10	4500
F007J-W512-364/FFC	3	5	6.4	1:0.5~1:1.3	1.2~4.0	5~7	UYX128GAS#10	4500
F007JD-W512-240/FFC	2	4	4.0	1:0.5~1:1.3	1.2~4.0	5~7	UYX128GAS#10	4500
F007JD-W512-248/FFC	2	4	4.8	1:0.5~1:1.3	1.2~4.0	5~7	UYX128GAS#10	4500
F007JD-W512-356/FFC	3	5	5.6	1:0.5~1:1.3	1.2~4.0	5~7	UYX128GAS#10	4500
F007JD-W512-364/FFC	3	5	6.4	1:0.5~1:1.3	1.2~4.0	5~7	UYX128GAS#10	4500



**DESCRIPTION**

**MECHANIC ELASTIC OR LACE ATTACHING**

Elastic feeding evenly length and elasticity controlled by gear set. For elastic or lace attaching smoothly and properly on women's underwears.



**OPTION**

DEVICE	MOTOR			TABLE
	Model	Clutch	Servo	
.FAC .FEC .LF-A	F007J	T32xxHx	T72xx	F007-T F007-T4
.FAC/LF-A .FEC/LF-A	F007JD	-	TA401xx T6400xx	

**STANDARD**



**FFC (J)**

**MECHANIC TYPE ELASTIC FEEDING DEVICE**

1. Elastic feeding evenly length and elasticity controlled by gear set.
2. Maximum feeding width of elastic is 2-1/2"

**Available Model:**

- C007J-W512, C007JD-W512
- C007J-W522, C007JD-W522
- F007J-W512, F007JD-W512
- F007J-W522, F007JD-W522