


							mm	mm	Needle No.	S.P.M. (Max)
F007J-W121-240/FHA	2	4	4.0	1:0.5~1:1.3	1.2~4.0	5~7			UYX128GAS# 10	6000
F007J-W121-248/FHA	2	4	4.8	1:0.5~1:1.3	1.2~4.0	5~7			UYX128GAS# 10	6000
F007J-W121-356/FHA	3	5	5.6	1:0.5~1:1.3	1.2~4.0	5~7			UYX128GAS# 10	6000
F007J-W121-364/FHA	3	5	6.4	1:0.5~1:1.3	1.2~4.0	5~7			UYX128GAS# 10	6000
F007JD-W121-240/FHA	2	4	4.0	1:0.5~1:1.3	1.2~4.0	5~7			UYX128GAS# 10	6000
F007JD-W121-248/FHA	2	4	4.8	1:0.5~1:1.3	1.2~4.0	5~7			UYX128GAS# 10	6000
F007JD-W121-356/FHA	3	5	5.6	1:0.5~1:1.3	1.2~4.0	5~7			UYX128GAS# 10	6000
F007JD-W121-364/FHA	3	5	6.4	1:0.5~1:1.3	1.2~4.0	5~7			UYX128GAS# 10	6000



DESCRIPTION

GENERAL LIGHT MATERIAL SEAMING/BOTTOM HEMMING

Regular cover stitching , can be attached with hemming set for various sewing. Such as plain seaming and bottom hemming for underwear, sportswear etc. (For light material)



OPTION

DEVICE	MOTOR			TABLE
.UTG				F007-T F007-T4
.UTH	Model	Clutch	Servo	
.UTJ				
.UTK	F007K	T32xxHx	T72xx T74xx	
.FV				
.FV/CSA			TA401xx	
.FV/CSB	F007JD	-	T6400xx	
.FV/TUB				

STANDARD



**FHA (J)
HEMMING DEVICE**

Suitable for the bottom hemming of T-shirt, underwear, cuff of children's garment...etc. Be able to adjust the width of hemming set to fit the demands, easy operation

Available Model:

- F007J-W121, F007JD-W121
- F007J-W122, F007JD-W122
- F007J-W123, F007JD-W123
- F007J-W162, F007JD-W162