

									
F007J-W222A-240/FQ/FEC	2	4	4.0	1:0.5~1:1.3	1.2~4.0	5~7	UYX128GAS#10	6000	
F007J-W222A-248/FQ/FEC	2	4	4.8	1:0.5~1:1.3	1.2~4.0	5~7	UYX128GAS#10	6000	
F007J-W222A-356/FQ/FEC	2	5	5.6	1:0.5~1:1.3	1.2~4.0	5~7	UYX128GAS#10	6000	
F007J-W222A-364/FQ/FEC	2	5	6.4	1:0.5~1:1.3	1.2~4.0	5~7	UYX128GAS#10	6000	
F007JD-W222A-240/FQ/FEC	2	4	4.0	1:0.5~1:1.3	1.2~4.0	5~7	UYX128GAS#10	6000	
F007JD-W222A-248/FQ/FEC	2	4	4.8	1:0.5~1:1.3	1.2~4.0	5~7	UYX128GAS#10	6000	
F007JD-W222A-356/FQ/FEC	2	5	5.6	1:0.5~1:1.3	1.2~4.0	5~7	UYX128GAS#10	6000	
F007JD-W222A-364/FQ/FEC	2	5	6.4	1:0.5~1:1.3	1.2~4.0	5~7	UYX128GAS#10	6000	



**DESCRIPTION**

**TAPE BINDING WITH TAPE CUTTER**

For tape binding on openings of leg or neck of underwear, T-shirt etc. Attached with electric tape cutter to save tape and increase sewing efficiency.

**OPTION**



DEVICE	MOTOR			TABLE
.FA	Model	Clutch	Servo	F007-T F007-T4
.FAC	F007J	T32xxHx	T72xx	
.FEC				
.FA/FAC	F007JD	-	TA401xx T6400xx	
.FA/FEC				

**STANDARD**



**FEC (J)**

**ELECTRIC TAPE CUTTING DEVICE**

1. With Knee-touched switch can drive the electric tape cutter to cut off the tape, elastic or lace, replace scissors, increase efficiency, and reduce elastic tape consumption.
2. Maximum cutting width of tape or elastic is 1-1/2".
3. Short cutter is available, please remark when ordering. EX: F007JD-W222A-356/FQ/FEC.

**Available Model:**

- F007J/FQ, F007JD/FQ
- F007J/FE, F007JD/FE
- F007J/FFC, F007JD/FFC
- F007J/FFD, F007JD/FFD
- F007J/FFP, F007JD/FFP
- F007J/FSP, F007JD/FSP
- F007J/FWP, F007JD/FWP

Self-installation : Y



**FQ (J)**

**TAPE BINDING**

1. For tape binding on openings of leg or neck of underwear, T-shirt etc.
2. If customer purchases machine with FQ, we will also attach FG. If customer purchases FQ device only, there won't be FG attached.
3. Ways to order the device:
  - (1) F007JD-W222-240/FQ.....includes the whole FQ device and FG subassembly
  - (2) F007JD-W222-240.....please note that it is only

equipped FQ gauge set, but no FQ subassembly or FG

(3) F007JD-W222-240/FQP....includes FQ and FG subassembly, but no binder

4.Binder's standard opening size is 1-3/8" wide and finished size is 1/2" wide in 3 folds. Please remark if need another size when ordering, but the delivery and cost need to be re-calculated.

**Available Model:**

F007J-W522,F007JD-W522