


							mm	mm	Needle No.
F007J-W222-240/FFP	2	4	4.0	1:0.5~1:1.3	1.2~4.0	5~7	UYX128GAS#10	6000	6000
F007J-W222-248/FFP	2	4	4.8	1:0.5~1:1.3	1.2~4.0	5~7	UYX128GAS#10	6000	6000
F007J-W222-356/FFP	3	5	5.6	1:0.5~1:1.3	1.2~4.0	5~7	UYX128GAS#10	6000	6000
F007J-W222-364/FFP	3	5	6.4	1:0.5~1:1.3	1.2~4.0	5~7	UYX128GAS#10	6000	6000
F007JD-W222-240/FFP	2	4	4.0	1:0.5~1:1.3	1.2~4.0	5~7	UYX128GAS#10	6000	6000
F007JD-W222-248/FFP	2	4	4.8	1:0.5~1:1.3	1.2~4.0	5~7	UYX128GAS#10	6000	6000
F007JD-W222-356/FFP	3	5	5.6	1:0.5~1:1.3	1.2~4.0	5~7	UYX128GAS#10	6000	6000
F007JD-W222-364/FFP	3	5	6.4	1:0.5~1:1.3	1.2~4.0	5~7	UYX128GAS#10	6000	6000



**DESCRIPTION**

**ELASTIC INSERTING & BINDING**

Elastic feeding evenly length and elasticity controlled by leaf spring with elastic tape side-motion controller for sewing the beginning and ending of elastic tape onto waistband, leg opening of briefs etc.



**OPTION**

DEVICE	MOTOR			TABLE
.FA				F007-T F007-T4
.LF-A				
.FAC	Model	Clutch	Servo	
.FEC	F007J	T32xxHx	T72xx	
.FAC/FA	F007JD	-	TA401xx T6400xx	
.FAC/LF-A				
.FAC/FA/LF-A				
.FEC/FA				
.FEC/LF-A				
.FEC/FA/LF-A				

**STANDARD**



**FFP (J)**

**MECHANIC TYPE ELASTIC FEEDING DEVICE & BINDING DEVICE (LEAF SPRING)**

1. Elastic feeding evenly length and elasticity controlled by leaf spring with elastic tape side-motion controller for sewing the beginning and ending of elastic tape onto waistband, leg opening of briefs etc.
2. Maximum acceptable size for the width of elastic is 1/8"to 1/4".

**Available Model:**

F007J-W222,F007JD-W222