







F13


								
F007K-W512-240/FFC	2	4	4.0	1:0.5~1:1.3	1.6~4.2	5	UYX128GAS#10	4500
F007K-W512-248/FFC	2	4	4.8	1:0.5~1:1.3	1.6~4.2	5	UYX128GAS#10	4500
F007K-W512-356/FFC	3	5	5.6	1:0.5~1:1.3	1.6~4.2	5	UYX128GAS#10	4500
F007K-W512-364/FFC	3	5	6.4	1:0.5~1:1.3	1.6~4.2	5	UYX128GAS#10	4500
F007KD-W512-240/FFC	2	4	4.0	1:0.5~1:1.3	1.6~4.2	5	UYX128GAS#10	4500
F007KD-W512-248/FFC	2	4	4.8	1:0.5~1:1.3	1.6~4.2	5	UYX128GAS#10	4500
F007KD-W512-356/FFC	3	5	5.6	1:0.5~1:1.3	1.6~4.2	5	UYX128GAS#10	4500
F007KD-W512-364/FFC	3	5	6.4	1:0.5~1:1.3	1.6~4.2	5	UYX128GAS#10	4500



DESCRIPTION

MECHANIC ELASTIC OR LACE ATTACHING

Elastic feeding ensures even length and elasticity controlled by gear set. For elastic or lace attaching smoothly and properly on women's underwears.



OPTION

DEVICE	MOTOR			TABLE
	Model	Clutch	Servo	
.FAC .FEC .LF-A .FAC/LF-A .FEC/LF-A	F007K	T32xxHx	T72xx	F007K-T
	F007KD	-	TA401xx T6421xx	

STANDARD



FFC (K)

MECHANIC TYPE ELASTIC FEEDING DEVICE

1. Elastic feeding evenly length and elasticity controlled by gear set.
2. Maximum feeding width of elastic is 2-1/2"

Available Model:

F007K-W512, F007KD-W512
F007K-W522, F007KD-W522