F14

							Needle No.	S.P.M. (Max)
F007K-W522-240/FR/FE	2	4	4.0	1:0.5~1:1.3	1.6~4.2	5	UYX128GAS#10	4500
F007K-W522-248/FR/FE	2	4	4.8	1:0.5~1:1.3	1.6~4.2	5	UYX128GAS#10	4500
F007K-W522-356/FR/FE	3	5	5.6	1:0.5~1:1.3	1.6~4.2	5	UYX128GAS#10	4500
F007K-W522-364/FR/FE	3	5	6.4	1:0.5~1:1.3	1.6~4.2	5	UYX128GAS#10	4500
F007KD-W522-240/FR/FE	2	4	4.0	1:0.5~1:1.3	1.6~4.2	5	UYX128GAS#10	4500
F007KD-W522-248/FR/FE	2	4	4.8	1:0.5~1:1.3	1.6~4.2	5	UYX128GAS#10	4500
F007KD-W522-356/FR/FE	3	5	5.6	1:0.5~1:1.3	1.6~4.2	5	UYX128GAS#10	4500
F007KD-W522-364/FR/FE	3	5	6.4	1:0.5~1:1.3	1.6~4.2	5	UYX128GAS#10	4500

DESCRIPTION

ELECTRIC ELASTIC OR LACE ATTACHING (with Right Fabric Trimmer)

Elastic feeding ensures even length and elasticity controlled by electric digital control box, with right hand side fabric trimmer for elastic or lace attaching smoothly and properly on women's underwears.



OPTION

DEVICE	MOTOR			TABLE
.FAC .FEC .LF-A .FAC/LF-A .FEC/LF-A	Model	Clutch	Servo	F007K-T1
	F007K	T32xxHx	T72xx	
	F007KD	-	TA401xx T6421xx	

STANDARD

FE (K)

ELECTRIC TYPE ELASTIC FEEDING

1. Elastic feeding evenly length and elasticity controlled by electronic digital control box.
2. Maximum feeding width of elastic is 2-1/2".

Available Model:

F007K-W512, F007KD-W512

F007J-W522, F007JD-W522

Self-installation : Y

FR (K)

RIGHT HAND SIDE TRIMMER

Right hand side waste fabric trimming, maks sewing quality better.

Available Model:

F007K-W522, F007KD-W522