	Į		.₩.	00	***************************************	mm	Needle No.	S.P.M. (Max)
F007K-U132-256/FHK	2	4	5.6	1:0.5~1:1.3	1.6~4.2	5	UYX128GAS#10	4500
F007KD-U132-256/FHK	2	4	5.6	1:0.5~1:1.3	1.6~4.2	5	UYX128GAS#10	4500







DESCRIPTION

2 NEEDLE 4 THREAD CUFF HEM & AUTOMATIC HEMMING DEVICE

- The pneumatic automatic feeding and folding device is for T-shirt cuffing and hemming, which can save manpower and upgrade he technique.
- Customers can adjust the width of hemming folding edge and the horizontal width between folding fabric and left needle as required. Since there is no need to cut the fabric in advance material cost can be saved.
- The electric eye can detect feeding, edging and presser foot lifter automatically. After finishing the action, the operation will stop automatically.
- 4. The maximum productivity: 6000 ~ 7000 pc(cuff)/8 hours

OPTION

DEVICE		TABLE			
	Model	Clutch	Servo		
-	F007K	-	T7421KH	F007K-T2	
	F007KD	-	T6427UHA-A		

STANDARD

FHK (K)

AUTOMATIC HEMMING DEVICE

- The pneumatic automatic feeding and folding device is for T-shirt cuffing and hemming, which can save manpower and upgrade he technique.
- Customers can adjust the width of hemming folding edge and the horizontal width between folding fabric and left needle on demand. Due to no need to cut the fabric in advance the material cost can be saved.
- 3. The electric eye can detect feeding, edging and presser foot lifter automatically. After finishing the action, the operation will stop automatically.
- 4. The maximum productivity: $6000 \sim 7000 \text{ pc(cuff)/9}$ hours