

					mm	mm	Needs No.	S.P.M. (Max)
F007K-W162-240/FHA	2	4	4.0	1:0.5~1:1.3	1.6~4.2	5/7	TVx5#14~#16	6000
F007K-W162-248/FHA	2	4	4.8	1:0.5~1:1.3	1.6~4.2	5/7	TVx5#14~#16	6000
F007K-W162-356/FHA	3	5	5.6	1:0.5~1:1.3	1.6~4.2	5/7	TVx5#14~#16	6000
F007K-W162-364/FHA	3	5	6.4	1:0.5~1:1.3	1.6~4.2	5/7	TVx5#14~#16	6000
F007KD-W162-240/FHA	2	4	4.0	1:0.5~1:1.3	1.6~4.2	5/7	TVx5#14~#16	6000
F007KD-W162-248/FHA	2	4	4.8	1:0.5~1:1.3	1.6~4.2	5/7	TVx5#14~#16	6000
F007KD-W162-356/FHA	3	5	5.6	1:0.5~1:1.3	1.6~4.2	5/7	TVx5#14~#16	6000
F007KD-W162-364/FHA	3	5	6.4	1:0.5~1:1.3	1.6~4.2	5/7	TVx5#14~#16	6000



DESCRIPTION

LONG NEEDLE BAR MOVEMENT GENERAL HEAVY MATERIAL SEAMING/BOTTOM HEMMING

Regular cover stitching, suitable for heavy material. Can attach hemming set for various sewing. Such as plain seaming and bottom hemming for underwear, sportswear, etc...



OPTION

DEVICE	MOTOR			TABLE
	Model	Clutch	Servo	F007K-T
.UTG	F007K	T32xxHx	T72xx	
.UTH			T74xx	
.UTJ				
.UTK	F007KD	-	TA401xx T6421xx	

STANDARD



FHA (K) HEMMING DEVICE

Suitable for the bottom hemming of T-shirt, underwear, cuff of children's garment...etc. Be able to adjust the width of hemming set to fit the demands, easy operation

Available Model:

- F007K-W121, F007KD-W121
- F007K-W122, F007KD-W122
- F007K-W123, F007KD-W123
- F007K-W162, F007KD-W162