Highlead GC20618-2

Twin Needle Flatbed Heavy Duty Compound Feed Walking foot Sewing Machine

(with Bottom feed, needle feed & walking foot top feed)



*Photo shows the GC20618-1 single needle version

The GC20618-2 is the twin needle version of Highlead's heavy duty compound feed walking foot lockstitch industrial sewing machine.

It is designed using large ${\bf vertical}$ axis rotating hook & bases for thread loop catching and sliding bars for thread up taking.

The machine is smooth running, durable, versatile and its robust construction includes: needle roller bearings for the arm & hook shaft etc., cog driven belt assemblies and more importantly an **auto oil lubrication system** is fitted, which reduces wear & tear considerably.

It features a heavy duty triple feeding action by way of: bottom feed, needle feed and walking foot top feed and is fitted with two large vertically mounted hook & bases for use with medium to heavy weight materials.

A safety clutch is fitted to help prevent damage to the hooks, bevel gears and other important parts, should the sewing machine become jammed or over-loaded.

The Highlead GC20618-2 is a twin needle, needle feed, walking foot industrial sewing machine for use on medium to heavy weight materials and is suited to sewing for example:

Inflatable products, bouncy castles, car seats, general upholstery and leather articles, belts, canvas, tents, awnings, lorry curtain sidings, handbags, outdoor wear, camping goods etc.





Needle gauge: 6.4mm standard (optional: 3.2, 4.8, 8, 9.5 & 12.7mm)

Available direct from our Manchester Warehouse

Features:

Specification:

P.Automatic head lubrication
P.Triple feeding action
P.Quality robust construction
P.Automatic hook lubrication
P.Long stitch feature
P.Long vertical axis hook & bases
P.Reverse stitch lever
P.Hook safety clutch
P.Quiet balanced head

EMax sewing speed: 2000rpm
EStitch length: 0-9mm
ENeedle bar stroke: 36mm
ETrake up stroke: 74.5mm
ETrasser foot lift by hand: 8mm
ETrasser foot lift by foot: 16mm
ETrasser foot lift by foot: 16mm
ETrasser foot lift by foot: 15mm
ETrasser foot lift by foot: 15mm
ETRASSER SERVICES LENGTH SERVICES LENGT