

Highlead GC20638

Twin Needle Flatbed Heavy Duty Sewing Machine with Split Needle bar

(with Bottom feed, needle feed & walking foot top feed)



The GC20638 is the twin needle version of Highlead's latest model of heavy duty compound feed lockstitch machine which features a very useful selectable split needle bar.

The special split needle bar is particularly useful when sewing corners or tight angular stitching and allows the operator, at the flick of a lever, to disengage one of the needle bars; so the machine can sew with one needle. You can select to disengage or re-engage the left or right needle depending on the type of corner you are doing.

The machine is smooth running, durable, versatile and its robust construction includes: needle roller bearings for the arm & hook shaft etc., cog driven belt assemblies and more importantly an **auto oil lubrication system** is fitted, which reduces wear & tear considerably.




As well as the split needle bar design, It features a heavy duty triple feeding action by way of: bottom feed, needle feed and walking foot top feed and is fitted with two large vertically mounted hook & bases for use with medium to heavy weight materials.

A safety clutch is fitted to help prevent damage to the hooks, bevel gears and other important parts, should the machine become jammed or over-loaded.

The GC20638 is a twin needle, needle feed, walking foot machine with split needle bar for use on medium to heavy weight materials and is suited to sewing for example:

Car seats, leather upholstery, general upholstery, leather goods, belts, canvas, tents, awnings, handbags, outdoor wear, Inflatable products, bouncy castles, shoe uppers (leather or synthetic leather), sports apparatus, office furniture, soft cushions etc.

Needle gauge: 8mm standard (9.5mm option)



Features:

- Split needle bar (selectable)
- Automatic head lubrication
- Triple feeding action
- Quality robust construction
- Automatic hook lubrication
- Long stitch feature
- Large vertical axis hook & bases
- Reverse stitch lever
- Hook safety clutch
- Quiet balanced head

Specification:

- Max sewing speed: 2000rpm
- Stitch length: 0-9mm
- Needle bar stroke: 33.4mm
- Presser foot lift by hand: 7mm
- Presser foot lift by foot: 13mm
- Hook: 2x large Vertical type
- Lubrication: Auto pump type