

Highlead GC24688-2D

Heavy Duty Twin Needle Post-Bed Sewing Machine with Walking Foot & Automatic Thread Trimmer



High Specification Walking Foot Post Bed with Automatic Thread Trimmer

Highlead's new GC24688-2D "top of the range" twin needle walking foot post-bed lockstitch sewing machine fully equipped with automatic thread trimmer, automatic reverse, automatic foot lifter, stitch program, dial adjustable walking foot, quick stroke adjustment, automatic lubrication and electronic servo needle position motor etc.

For use in many sections of the heavy duty industry including the manufacture & topstitching of high-end house hold upholstery, office furniture, car upholstery & interiors, leather goods, filters, technical textiles, plastic and laminated products etc.


The post bed design gives you greater access and control when sewing decorative (top stitching) & functional stitching on shaped or 3d items, which would normally be difficult or impossible to sew on a standard flat bed machine.

Its heavy duty triple feeding action by way of: bottom feed, needle feed and walking foot top feed, guarantees effective handling of medium/heavy weight materials and fabrics.

Designed to meet high quality and high performance demands with expert operator aids and devices fitted as standard.

Optional pneumatic seam centre guide available combined with special sewing foot.

Machine supplied complete on unit stand with slant base board and quality electronic control equipment and drive motor manufactured by Mitsubishi in Japan



Features:

- Versatile Post Bed Shape
- Twin needle lockstitch sewing.
- Bottom feed, needle feed + top walking foot feed.
- Automatic thread trimmer
- Automatic reverse back-tack
- Automatic foot-lifter
- Quick presser foot stroke adjuster
- Easy under arm operator controls.
- Vertical large hook & bases
- 170mm Post bed height
- Automatic lubrication.
- Up-to 9mm stitch feature.



Easy to operate top dial adjusts the alternating presser foot movement and automatically sets the corresponding sewing speed.



Specification:

- Max sewing speed: 2400rpm
- Stitch length: 0-9mm
- Needle bar stroke: 34mm
- Post bed height: 170mm
- Feed system: Triple
- Presser foot lift by hand: 10mm
- Presser foot lift by foot: 16mm
- Presser foot alternation: 1-7mm
- Needle gauge standard: 8mm (10,12mm option)
- Motor: 750W servo electronic

Single needle post bed models also available:

Highlead GC24688-1L-D Single needle post-bed with walking foot and automatic thread trimmer (Left-side stitching)

Highlead GC24688-1R-D Single needle post-bed with walking foot and automatic thread trimmer (Right-side stitching)