

## Highlead GM288

### High Speed Industrial Overlock Sewing Machine



Highlead GM288

Highlead GM288 series high speed overlock sewing machine in 2 thread, 3 thread, 4 thread or 5 thread versions.

New design with improved feeding mechanism for better overall performance and increased versatility.

Fully enclosed oil system with running speeds at up-to 6500 stitches per minute.

Smooth & quiet operation using a robust balanced sewing head with easy to use operator adjustments such as stitch size and feeder movement.

Different Sub-classes available including Light, Light-Medium & medium-heavy models suited to different sections of the clothing & textile industry.

**Now on show in our warehouse, customers are welcome to come and try it.**



#### Features:

- Full automatic enclosed oil system
- Silicone needle cooling device
- Differential feed adjusting lever
- Dial adjusting stitch regulator
- Balanced quiet sewing head

#### Specification:

- Max sewing speed: 6500spm
- Stitch length: 1-3.6mm
- Presser foot lift 6.5mm
- Needle standard B27
- Other specs. subject to sub-class

Model	Application	Number of needle	Number of thread	Stitch code	Stitch length	stitch width	Needle gauge	Differential ratio	Presser foot lift	Max Sewing speed
GM288-2	Butted seaming for dyeing	1	2	503	1.0-3.6mm	7mm		1:1.29-1:0.6	6.5mm	6500r.p.m.
GM288-3	standard	1	3	504	1.0-3.6mm	4mm		1:1.29-1:0.6	6.5mm	6500r.p.m.
GM288-4	standard	2	4	514	1.0-3.6mm	6.2mm	2.2mm	1:1.29-1:0.6	6.5mm	6500r.p.m.
GM288-5	standard	2	5	516	1.5-3.6mm	7mm	3mm	1:1.29-1:0.6	6.5mm	6500r.p.m.
GM288-6	standard	3	6	543	1.5-3.6mm	10.0mm	4.8mm	1:1.29-1:0.6	6.5mm	6500r.p.m.
GM288-301	Heavy duty overlock	1	3	504	1.0-3.6mm	5mm		1:1.29-1:0.6	6.5mm	6500r.p.m.
GM288-302	Blind hemming	1	3	505	1.0-3.6mm	4mm		1:1.29-1:0.6	6.5mm	6500r.p.m.
GM288-304	Fine edging	1	3	504	1.0-3.6mm	2mm		1:1.29-1:0.6	6.5mm	6500r.p.m.
GM288-401	tape inserting	2	4	514	1.0-3.6mm	6.2mm	2.2mm	1:1.29-1:0.6	6.5mm	6500r.p.m.
GM288-501	Jeans overlock (14 oz.)	2	5	516	1.5-3.6mm	9.8mm	4.8mm	1:1.29-1:0.6	6.5mm	6500r.p.m.
GM288-502	Wide seam jeans overlock (14 oz.)	2	5	516	1.5-3.6mm	11.8mm	4.8mm	1:1.29-1:0.6	6.5mm	6500r.p.m.
GM288-503	Medium heavy duty overlock	2	5	516	1.5-3.6mm	7mm	3mm	1:1.29-1:0.6	6.5mm	6500r.p.m.
GM288-504	Wide seam medium heavy duty overlock	2	5	516	1.5-3.6mm	9.8mm	4.8mm	1:1.29-1:0.6	6.5mm	6500r.p.m.
GM288-505	Heavy duty overlock	2	5	516	1.5-3.6mm	9.8mm	4.8mm	1:1.29-1:0.6	6.5mm	6500r.p.m.
GM288-506	Wide seam heavy duty overlock	2	5	516	1.5-3.6mm	11.8mm	4.8mm	1:1.29-1:0.6	6.5mm	6500r.p.m.

\*Standard sub-class models listed above, other versions and special converted models also available