

747K-514M5-23/BK	2	4	2	3   5	0.7-2	3.6	6	DCX27#11	7500	S.P.M. (Max)
747KD-514M5-23/BK	2	4	2	3   5	0.7-2	3.6	6	DCX27#11	7500	S.P.M. (Max)



**DESCRIPTION**

**BACK LATCHING SEAMING**

To prevent seam looseness, turn over the thread and then insert into overlock seaming at the beginning of sewing. For sleeve and sideways sewing of underwear, sportswear etc.

Remark :

To equip with Servo motor for needle position function is optional and recommended.



**OPTION**

DEVICE	MOTOR/TABLE			
	Model	Clutch	Servo	Table
700K	T32xx	CSC-T36xx	TB221GHE	700K-T
	T72xx			700K-T1/TBK
700KD	-	-	TB201UHBE	700KD-T
				700KD-T2/TBKD-1

- Feature
- FAQ
- Parts Download

**STANDARD**



**BK  
BACK LATCHING**

To prevent seam looseness, turn over the thread and then insert into overlock seaming at the beginning of sewing

- . KD207 Hand wheel: Standard equipment of 700K/BK machine, optional for BK device selling
- . BK232 Sewing bed : optional for BK device selling.

**Available Model:**

- 737K-504M5, 737KD-505M5
- 747K-514M5, 747KD-514M5