	
747DFT-514H4-24/GB	2	4	2	4 6	0.7-2	3.6	6	DCX27# 11	5000
757DFT-516H4-35/GB	2	5	3	5 8	0.7-2	3.6	6	DCX27# 14	5000
757DFT-516H4-56/GB	2	5	5	6 11	0.7-2	3.6	6	DCX27# 14	5000




DESCRIPTION

FRONT TOP-FEED GATHERING

Intermittently gathering on both upper and lower plies of fabric, It can also be operated separately to gather either upper or lower ply of fabric, Knee controller mainly controls the gathering on the upper ply of fabric.

Remark :

Piping Binder (Tape width 25mm, finished size 6mm)



OPTION

DEVICE	CLUTCH MOTOR	SERVO MOTOR	TABLE
.P .DT .P/DT .DT/CSA .P/DT/CSA .DT/CSB .P/DT/CSB .DT/TUB .P/DT/TUB	T32xx CSC-T36XX	TB221GH T72xx	747-T

STANDARD



GB

GATHERING DEVICE FOR TOP FEED MODEL

Continuous or intermittent random gathering on lower ply, for top feed model.

P: Piping Folder KV57 (tape width 25mm/ finish width 6mm) is optional. For piping with rope inside, presser foot requires a trench, which is marked with P at the end of parts code. e.g. P463P.

Available Model:

747DFT-514H4, 757DFT-516H4