

					
L918-L1	29.0	0-4	Hand: 5.5 / Auto: 10~13	DAX1#9~#10	4000
L918-M1	30.7	0-5	Hand: 5.5 / Auto: 10~13	DBX1#11~#14	4000~4500
L918-H1	35.0	0-6	Hand: 5.5 / Auto: 10~13	DBX1#20~#23	3500~4000
L918-BM1	30.7	0-5	Hand: 5.5 / Auto: 10~13	DBX1#11~#14	4000~4500
L918-DM1	30.7	0-4	Hand: 5.5 / Auto: 10~13	DBX1#11~#14	4000
L918-BH1	35.0	0-6	Hand: 5.5 / Auto: 10~13	DBX1#20~#23	3500~4000
L918-HM1	35.0	0-6	Hand: 5.5 / Auto: 10~13	DBX1#20~#23	3500~4000
L918-NH1	30.7	0-5	Hand: 5.5 / Auto: 10~13	DBX1#20~#23	3500~4000
L918-NM1	30.7	0-4	Hand: 5.5 / Auto: 10~13	DBX1#9~#18	4000~4500
L918-RM1	30.7	0-5	Hand: 5.5 / Auto: 10~13	DBX1#11~#14	4000~4500

DESCRIPTION

L918-M1/L918-M1-13

The latest sewing mechanisms / High speed single needle needle feed lockstitch machine & automatic thread trimmer

- . For medium / heavy material.
- . The optimum and elegant machine head was created, using the latest sewing mechanisms in order to achieve low-tension sewing. The machine flexibly responds to a wide range of materials and produces beautiful seams of steady quality.
- . Adopts the built-in reverse feeding solenoid, noise is soft, maintenance is easy, and strengthens durability of the machine.

L918-BM1-13 / L918-BH1-13

High speed single needle lockstitch machine(with automatic rotary thread trimmer)

- . For medium / heavy material.
- . Applied with rotary trimming mechanism, the trimming result is perfect. It reduces the consumption of thread, decreases the frequency of bobbin changing, and increases sewing efficiency.

L918-NM1/L918-NM1-13

High speed single needle needle feed lockstitch machine & automatic thread trimmer machine

- . For medium / heavy material.
- . When the needle penetrates the material, the needle and feed dog feed the material synchronously, minimizing material slippage. It is suitable for sewing Slippery or multiple-laid materials. Stitch-length is precise, and stitching is excellent.

L918-DM1/L918-DM1-13

Micro lubrication high speed single needle Lockstitch machine & automatic thread trimmer machine

- . For medium material.
- . Oil free for the head, so there will be no blackness or greasiness on the fabric and thread. Satisfy customer's demand for high sewing quality.

L918-RM1/L918-RM1-13

High speed vertical edge trimmer single needle lockstitch machine & automatic thread trimmer machine

- . For medium material.
- . This machine lets you sew and cut the fabric at the



same time, When turning the knob up, this machine
 Can be used for ordinary lockstitch machine. This
 function lets you change easily between normal sewing
 and cutting while sewing.

Sub-class	32	40	48	64	85
Gauge Width	1/8"	5/32"	3/16"	1/4"	3/8"
EX: L918-RM1-32-13					

OPTION

Clutch Motor	Auto Tread Trimmer Machine (Function Option)						Table
	No.	Control Panel	No.	Reverse Feeding	Wiper	Auto Lifter	
T32xHx (general M/C without thread trimmer)	0	-	0	V	-	-	TA122EH
	0	-	1	V	V	-	TA122EH
	1	L-900	2	V	-	V	TA122EH
	1	L-900	3	V	V	V	TA122EH
EX: L918-M1-1 3							