

SKM series

Features

- Large and transverse horizontal axis rotary hook.
- Standard presser foot is flat type.

Specifications (SKM-□)

Variety	26	36
Number of needle	Two needle	Three needle
Max. sewing speed	800(s.p.m.)	
Max. stitch length	5/16" (8 mm)	
Clearance under presser foot	by knee	7/16" (11 mm)
	by hand	25/64" (10 mm)
Needle bar stroke	1-31/32" (50 mm)	
Needle(standard)	DDx1 (#25) , 328 (#200)	
Thread	#2~#00	
Hook	Large horizontal axis hook	
Thread take up lever	Link type	
Lubrication	Hand type	
Bed size	20-33/64" x 9-59/64" (521 x 252 mm)	
Working space	10"x 7-43/64" (254 x 195 mm)	
Motor	Clutch motor	
Net weight(Head only)	44Kg	

Needle gauge size

Variety	Available needle gauge size range
26	5 mm(13/64"), 5.5 mm(7/32"), 7.5 mm(19/64") standard 7.5 mm(19/64")
36	2.75-2.75 mm(7/64"-7/64") 3-3 mm(1/8"-1/8") 3.75-3.75 mm (9/64"-9/64") standard 3.75-3.75 mm (9/64"-9/64")

Finger guard (at extra charge)

Parts No.	Variety
1897	26 , 36