

SLH series

Features

- Large barrel shuttle
- Extra long arm (Working space 413 mm)
- Long stitch length (15 mm max.)
- Reverse stitching by stitch adjusting lever or foot pedal
- Cam take-up type makes perfect stitching
- Synchronized walking foot and drop feeding mechanism assures uniform stitching
- Extra high presser foot lift for sewing extra heavy materials
- Suitable for extra thick threads (#0 #00)
- Automatic back tack (BT) and presser foot lift (FL) available





Large bobbin

SLH-2B

Specifications (SLH-□)

Variety		2B	2B-FH-1
Number of needle		Single needle	
Max. sewing speed		700 s.p.m.	
Max. stitch length		19/32" (15 mm)	
Clearance under presser foot	by pedal	1-7/64" (28 mm)	1-17/64" (32 mm)
	by hand	29/32" (23 mm)	1-9/64" (29 mm)
Needle bar st	roke	2-15/64" (56.7 mm)	2-19/32" (66 mm)
Needle(standard)		Schmetz 1000 (#250)	
Thread		#0 (standard) ~ #00	
Hook		Large shuttle hook	
Amount of lift of alternating		3/16"-9/32" standard 15/64"	
presser foot		(5 - 7 mm) (standard 6 mm)	
Thread take up lever		Cam type	
Lubrication		Hand type	
Bed size		25-3/4" x 10-5/32"	(654 x 258 mm)
Working space		16-1/4"x 8-37/64"	(413 x 218 mm)
Motor		Clutch motor	
Net weight(Head only)		105kg	