



	 mm	 mm	 mm	 Needle No.	 S.P.M. (Max)
T828-42-xxxMx	29.0	4	Hand: 7 / Auto: 10	DPX5 #14	4000
T828-42-xxxHx	30.7	5	Hand: 7 / Auto: 10	DPX5 #22	3000
T828-45-xxxMx	35.0	4	Hand: 7 / Auto: 10	DPX5 #14	4000
T828-45-xxxHx	30.7	5	Hand: 7 / Auto: 10	DPX5 #22	3000
T828-47-xxxLx	30.7	4	Hand: 7 / Auto: 10	DPX5 #11	4000
T828-48-xxxLx	35.0	5	Hand: 7 / Auto: 10~13	DPX5 #11	3000
T828-72-xxxMx	35.0	7	Hand: 7 / Auto: 10~13	DPX5 #14	3000
T828-72-xxxHx	30.7	7	Hand: 7 / Auto: 10~13	DPX5 #22	3000
T828-75-xxxMx	30.7	7	Hand: 7 / Auto: 10~13	DPX5 #14	3000
T828-75-xxxHx	30.7	7	Hand: 7 / Auto: 10~13	DPX5 #22	3000



DESCRIPTION

General Plan Seaming

- The design of needle feed mechanism moves with simple operation, excellent stitching and precise stitch-length.
- Adopting fully rotating horizontal axis hook, slide type thread take-up as well automatically lubricating system.
- Convenient window for monitoring bobbin thread volume.



OPTION

Clutch Motor	Auto Tread Trimmer Machine (Function Option)						Table
	No	Control Panel	Reverse Feeding	Wiper	Auto Lifter	Servo Motor	
T32xDx (general M/C without thread trimmer)	No	C-300M-A2	V	V	ELECTRIC	T710xEH	T828 -T1
	CP	C-300M-A2	V	V	PNEUMATIC	T710xEH	
EX: T828-42-064M/CP							