


## TE/TF series

- Suitable for sewing of high-class products, due to the feature of the oscillating hook, which ensures perfect seam tightness.



- Cloth plate for flat work available at extra charge (Part no. 8136C)



### Specifications (TE-□/TF-□)

Variety	TE-6	TE-6B	TF-6	TF-6B
Number of needle	Single needle			
Max. sewing speed	1,400(s.p.m.)			
Max. stitch length	15/64" (6 mm)	13/64" (5 mm)	13/64" (5 mm)	5/32" (4 mm)
Clearance under presser foot	25/64" (10 mm)			
	9/32" (7mm)			
Needle bar stroke	1-27/64" (36 mm)			
Needle(standard)	DB×1 (#19) 16×231 (#120)		TF×2 (#11) 34LL (#75)	
Thread	#20 (standard)		#40 (standard)	
Hook	Long beak oscillating shuttle hook			
Presser foot	standard	Narrow toe		Roller
	Accessories	Roller		Narrow toe
Thread take up lever	Cam type			
Lubrication	Hand type			
Cylinder size	2-27/64" (61.5 mm) dia.		2-1/2" (63.5 mm) dia.	
Working space	11-1/32"x 5-5/16" (280 x 135 mm)		11-1/32"x 5-33/64" (280 x 140 mm)	
Motor	Clutch motor			
Net weight(Head only)	18Kg		21Kg	