	
			mm	mm	Needle No.	S.P.M. (Max)	
VC008-04064P/VCE	4	8	1/4"(6.4mm)	1.4~3.6	12	UO113#11~#14	4500
VC008-04085P/VCE	4	8	1/3"(8.5mm)	1.4~3.6	12	UO113#11~#14	4500
VC008-04095P/VCE	4	8	3/8"(9.5mm)	1.4~3.6	12	UO113#11~#14	4500
VC008-04106P/VCE	4	8	5/12"(10.6mm)	1.4~3.6	12	UO113#11~#14	4500
VC008-04127P/VCE	4	8	1/2"(12.7mm)	1.4~3.6	12	UO113#11~#14	4500




DESCRIPTION

ELASTIC INSERTING/ATTACHING

Inserting and attaching elastic on waistband of jogging suits, sportswear or shirts etc., two kinds of sewing functions are available:

- (1) To attach tubular seamless elastic waistband.
- (2) To cover sewing on elastic after overlock seaming.



OPTION

DEVICE	CLUTCH MOTOR	SERVO MOTOR	TABLE
.VUT			
.VUT/VAD	T32xx	T6424EH	VC008-T1
.RL		T7119CH	VC008-T2
.VUT/VAD/RL			

STANDARD



VCE

TUBULAR ELASTIC INSERTING AND ATTACHING

Tubular elastic inserting on sports wear or man's underwear, two types of sewing functions are available:

- 1.To attach tubular seamless elastic waistband.
- 2.To cover sewing on elastic after overlock seaming.

Available Model:

VC008