V12

			→ ←	######################################	mm	Needle No.	S.P.M. (Max)
VC008-04064P/VWL	4	8	1/4"(6.4mm)	1.4~3.6	12	UO113#11~#14	4000
VC008-04085P/VWL	4	8	1/3"(8.5mm)	1.4~3.6	12	UO113#11~#14	4000
VC008-04095P/VWL	4	8	3/8"(9.5mm)	1.4~3.6	12	UO113#11~#14	4000
VC008-04106P/VWL	4	8	5/12"(6.4mm)	1.4~3.6	12	UO113#11~#14	4000
VC008-04127P/VWL	4	8	1/2"(12.7mm)	1.4~3.6	12	UO113#11~#14	4000



DESCRIPTION

ELASTIC ATTACHING (WITH BINDER B413)

Elasticity and length feeding can be accurately controlled according to sewing speed of machine. Easy operation for elastic inserting and attaching on waistband of jogging pants, sport-wear, briefs etc.

Remark:

elastic type size 38mm for Binder B413





OPTION



DEVICE	CLUTCH MOTOR	SERVO MOTOR	TABLE
.FH	T32xx	T6424EH T7119CH	VC008-T5

STANDARD



VWL/VWLB/VWLC FRONT ELASTIC FEEDING

Length of elastic type can be easily adjusted by elastic feeding device, suitable for sports pants and casual paints. Roller maintains the tension of elastic thread and quality during sewing process.

Remark: VWL with binder B413

VWLB with binder B411 and extending roller VWLC with VCE fabric guide

Available Model:

VC008-04064P, VC008-04085P, VC008-04095P, VC008-04106P, VC008-04127P,VC008-12048P, VC008-12064P