

			mm	mm	Needle No.	S.P.M. (Max)
VC008-04064P/VWLC	4 8	1/4"(6.4mm)	1.4~3.6	12	UO113#11~#14	4000
VC008-04085P/VWLC	4 8	1/3"(8.5mm)	1.4~3.6	12	UO113#11~#14	4000
VC008-04095P/VWLC	4 8	3/8"(9.5mm)	1.4~3.6	12	UO113#11~#14	4000
VC008-04106P/VWLC	4 8	5/12"(10.6mm)	1.4~3.6	12	UO113#11~#14	4000
VC008-04127P/VWLC	4 8	1/2"(12.7mm)	1.4~3.6	12	UO113#11~#14	4000
VC008-12048P/VWLC	12 24	3/16"(4.8mm)	1.4~3.6	12	UO113#11~#14	4000
VC008-12064P/VWLC	12 24	1/4"(6.4mm)	1.4~3.6	12	UO113#11~#14	4000



DESCRIPTION

ELASTIC INSERTING / ATTACHING (with VCE fabric guide)

Elasticity and length feeding can be accurately controlled according to sewing speed of machine. Easy operation for elastic inserting and attaching on waistband of jogging pants, sportswear, briefs etc.



OPTION

DEVICE	CLUTCH MOTOR	SERVO MOTOR	TABLE
.FH	T32xx	T6424EH T7119CH	VC008-T5

STANDARD



**VWL/VWLB/VWLC
FRONT ELASTIC FEEDING**

Length of elastic type can be easily adjusted by elastic feeding device, suitable for sports pants and casual pants. Roller maintains the tension of elastic thread and quality during sewing process.

Remark:VWL with binder B413

VWLB with binder B411 and extending roller

VWLC with VCE fabric guide

Available Model:

VC008-04064P, VC008-04085P,
VC008-04095P, VC008-04106P,
VC008-04127P, VC008-12048P,
VC008-12064P