

							
			mm	mm	Needle No.	S.P.M. (Max)	
VC008-0448-191P	4 8	3/16-3/4-3/16"	(4.8-19.1-4.8mm)	1.4~3.6	12	UO113#11~#14	4500
VC008-0448-222P	4 8	3/16-7/8-3/16"	(4.8-22.2-4.8mm)	1.4~3.6	12	UO113#11~#14	4500
VC008-0448-254P	4 8	3/16-1-3/16"	(4.8-25.4-4.8mm)	1.4~3.6	12	UO113#11~#14	4500
VC008-0464-191P	4 8	1/4-3/4-1/4"	(6.4-19.1-6.4mm)	1.4~3.6	12	UO113#11~#14	4500
VC008-0464-127P	4 8	1/4-1/2-1/4"	(6.4-12.7-6.4mm)	1.4~3.6	12	UO113#11~#14	4500
VC008-0464-254P	4 8	1/4-1-1/4"	(6.4-25.4-6.4mm)	1.4~3.6	12	UO113#11~#14	4500



DESCRIPTION

**GENERAL SEAMING
(4 Needles Unequal Needle Gauge)**

Cylinder bed automatic oiling, back and forth loopers driving mechanism, suitable for decorative sewing on high quality dress or tubular goods.



OPTION

DEVICE	CLUTCH MOTOR	SERVO MOTOR	TABLE
.VCE .VAD .VCE/VAD	T32xx	T6424EH T7119CH	VC008-T1 VC008-T2